

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street SE Charleston, WV 25304 (304) 926-0450 (304) 926-0452 fax Earl Ray Tomblin, Governor Randy C. Huffman, Cabinet Secretary www.dep.wv.gov

December 03, 2013

WELL WORK PERMIT

Horizontal 6A Well

This permit, API Well Number: 47-10302971, issued to EQT PRODUCTION COMPANY, is evidence of permission granted to perform the specified well work at the location described on the attached pages and located on the attached plat, subject to the provisions of Chapter 22 of the West Virginia Code of 1931, as amended, and all rules and regulations promulgated thereunder, and to all conditions and provisions outlined in the pages attached hereto. Notification shall be given by the operator to the Oil and Gas Inspector at least 24 hours prior to the construction of roads, locations, and/or pits for any permitted work. In addition, the well operator shall notify the same inspector 24 hours before any actual well work is commenced and prior to running and cementing casing. Spills or emergency discharges must be promptly reported by the operator to 1-800-642-3074 and to the Oil and Gas inspector.

Please be advised that form WR-35, Well Operators Report of Well Work is to be submitted to this office within 90 days completion of permitted well work, as should form WR-34 Discharge Monitoring Report within 30 days of discharge of pits, if applicable. Failure to abide by all statutory and regulatory provisions governing all duties and operations hereunder may result in suspension or revocation of this permit and, in addition, may result in civil and/or criminal penalties being imposed upon the operators.

In addition to the applicable requirements of this permit, and the statutes and rules governing oil and gas activity in WV, this permit may contain specific conditions which must be followed. Permit conditions are attached to this cover letter.

Per 35CSR-4-5.2.g this permit will expire in two (2) years from the issue date unless permitted well work is commenced. If there are any questions, please feel free to contact me at (304) 926-0499 ext. 1654.

James Martii

Chief

Operator's Well No: WV 514385

Farm Name: COASTAL FOREST RESOURCES

API Well Number: 47-10302971

Permit Type: Horizontal 6A Well

Date Issued: 12/03/2013

Promoting a healthy environment.

API Number: 103-0297 |

PERMIT CONDITIONS

West Virginia Code § 22-6A-8(d) allows the Office of Oil and Gas to place specific conditions upon this permit. Permit conditions have the same effect as law. <u>Failure to adhere to the specified permit</u> conditions may result in enforcement action.

CONDITIONS

- 1. This proposed activity may require permit coverage from the United States Army Corps of Engineers (USACOE). Through this permit, you are hereby being advised to consult with USACOE regarding this proposed activity.
- 2. If the operator encounters an unanticipated void, or an anticipated void at an unanticipated depth, the operator shall notify the inspector within 24 hours. Modifications to the casing program may be necessary to comply with W. Va. Code § 22-6A-5a (12), which requires drilling to a minimum depth of thirty feet below the bottom of the void, and installing a minimum of twenty (20) feet of casing. Under no circumstance should the operator drill more than fifty (50) feet below the bottom of the void or install less than twenty (20) feet of casing below the bottom of the void.
- 3. When compacting fills, each lift before compaction shall not be more than 12 inches in height, and the moisture content of the fill material shall be within limits as determined by the Standard Proctor Density test of the actual soils used in specific engineered fill, ASTM D698, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort, to achieve 95 % compaction of the optimum density. Each lift shall be tested for compaction, with a minimum of two tests per lift per acre of fill. All test results shall be maintained on site and available for review.
- 4. Operator shall install signage per § 22-6A-8g (6) (B) at all source water locations included in their approved water management plan within 24 hours of water management plan activation.
- 5. Oil and gas water supply wells will be registered with the Office of Oil and Gas and all such wells will be constructed and plugged in accordance with the standards of the Bureau for Public Health set forth in its Legislative rule entitled *Water Well Regulations*, 64 C.S.R. 19. Operator is to contact the Bureau of Public Health regarding permit requirements. In lieu of plugging, the operator may transfer the well to the surface owner upon agreement of the parties. All drinking water wells within fifteen hundred feet of the water supply well shall be flow tested by the operator upon request of the drinking well owner prior to operating the water supply well.
- 6. Pursuant to the requirements pertaining to the sampling of domestic water supply wells/springs the operator shall, no later than thirty (30) days after receipt of analytical data provide a written copy to the Chief and any of the users who may have requested such analyses.
- 7. If any explosion or other accident causing loss of life or serious personal injury occurs in or about a well or well work on a well, the well operator or its contractor shall give notice, stating the particulars of the explosion or accident, to the oil and gas inspector and the Chief, within 24 hours of said accident.
- 8. During the casing and cementing process, in the event cement does not return to the surface, the oil and gas inspector shall be notified within 24 hours.

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS W.VA. CODE \$22-6A - WELL WORK PERMIT APPLICATION

Well Operator: EQT Produc	tion Company		Operator ID	L 103 County	District	548 Quadrangle
			Operator ib	County	District	Quadrangle
Operator's Well Number:		514385	· · · · · · · · · · · · · · · · · · ·	_Well Pad Nam	ne	PNG129
Farm Name/Surface Owner :		Lacock		Public Road A	ccess: Lo	wman Ridge Road
Elevation, current ground:	1,328.0	_ Eleva	tion, proposed p	oost-construction	: 1,328	.0
Well Type: (a) Gas	Oil	Ur	derground Stor	age	·	
Other					······································	
(b) If Gas:	Shallow	•	Deep			
	Horizontal	•				
Existing Pad? Yes or No:	Yes					
Target formation is Marcellu Proposed Total Vertical Depth:		o www.mo.umx		7,318	parce target press	3010 01 4000 1 31
Formation at Total Vertical Dep				Marcellus		
) Proposed Total Measured De	pth			11,839		
Proposed Horizontal Leg Leng	yth			2,751		
Approximate Fresh Water Str	ata Depths:			620, 656, 680	, 731	
Method to Determine Fresh W	/ater Depth:			By offset we	ells	
Approximate Saltwater Depths				2013, 2362		
) Approximate Coal Seam Dept		· · · · · · · · · · · · · · · · · · ·		65, 1035, 1049,	1077	
Approximate Depth to Possibl 17)Does proposed well location					None repo	orted V
adjacent to an active mine?						
(a) If Yes, provide Mine Info:	Name:		· . · · · · · · · · · · · · · · · · · ·			
	Depth:					
	Seam:					
	Owner:					

Page 1 of 3

RICENED
CES CICILIA Cas
NOV 012013

Elizabeth and the Production

CASING AND TUBING PROGRAM

8) 'YPE	Size	New	Grade	Weight per	FOOTAGE:	INTERVALS:	CEMENT:
		or Used		<u>ft.</u>	for Drilling	Left in Well	Fill- up (Cu.Ft.)
conductor	20	New	MC-50	81	40	40	38 CD
resh Water	13 3/8	New	MC-50	54	831	831	727 CTS
coal							
ntermediate	9 5/8	New	MC-50	40	3,385	3,385	1,330 (T5
roduction	5 1/2	New	P-110	20	11,839	11,839	See Note 1
ubing	2 3/8		J-55	4.6			May not be run, if run will be set 100' less than TD
iners							

DMH 10-28-13

YPE	<u>Size</u>	Wellbore Diameter	<u>Wall</u> Thickness	<u>Burst</u> <u>Pressure</u>	Cement Type	Cement Yield (cu. ft./k)
Conductor	20	24	0.375	•	Construction	1.18
resh Water	13 3/8	17 1/2	0.38	2,480	1	1.21
oal						
ntermediate	9 5/8	12 3/8	0.395	3,590	1	1.21
roduction	5 1/2	8 1/2	0.361	12,640	-	1.27/1.86
ubing						·····
iners						

Packers

		 Т	
ind:	N/A		
izes:	N/A		
epths Set:	N/A		

lote 1: EQT plans to bring the TOC on the production casing cement job 1,000' above kick off point, which is at last 500' above the shallowest production zone, to avoid communication.

Page 2 of 3

PECEMED

Cilico di Uli Liui Cas

107 Al 103

Ele cia cia cia cia cia

(3/13)

19) Describe proposed well work, including the drilling and plugging back of any pilot hole:
Drill and Complete a new horizontal well in the Marcellus formation. The vertical drill to go down to an approximate depth of
4145' then kick off the horizontal leg into the marcellus using a slick water frac.
20) Describe fracturing/stimulating methods in detail, including anticipated max pressure and max rate:
Hydraulic fracturing is completed in accordance with state regulations using water recycled from previously fractured wells and obtained from freshwater sources. This water is mixed with sand and a small percentage (less than 0.3%) of chemicals (including 15% Hydrochloric acid,
gelling agent, gel breaker, friction reducer, biocide, and scale inhibitor), referred to in the industry as a "slickwater" completion. Maximum
anticipated treating pressures are expected to average approximately 8500 psi, maximum anticipated treating rates are expected to average approximately 100 bpm. Stage lengths vary from 150 to 300 feet. Average approximately 200,000 barrels of water per stage. Sand sizes
vary from 100 mesh to 20/40 mesh. Average approximately 200,000 pounds of sand per stage.
21) Total area to be disturbed, including roads, stockpile area, pits, etc, (acres): no additional disturbance
22) Area to be disturbed for well pad only, less access road (acres): no additional disturbance
 23) Describe centralizer placement for each casing string. Surface: Bow spring centralizers – One at the shoe and one spaced every 500'.
Intermediate: Bow spring centralizers – One cent at the shoe and one spaced every 500'. Intermediate: Bow spring centralizers – One cent at the shoe and one spaced every 500'.
Production: One spaced every 1000' from KOP to Int csg shoe
24) Describe all cement additives associated with each cement type. Surface (Type 1 Cement): 0-3% Calcium Chloride
Used to speed the setting of cement slurries.
0.4% flake. Loss Circulation Material (LCM) is used to combat the loss of the cement sturry to a thief zone. Intermediate (Type 1 Cement): 0-3% Calcium Chloride. Salt is used in shallow, low temperature formations to speed the setting of cement
slurries. 0.4% flake. Loss Circulation Material (LCM) is used to combat the loss of whole drilling fluid or cement slurry (not filtrate)
to a thief zone.
Production:
<u>Lead (Type 1 Cement)</u> : 0.2-0.7% Lignosulfonate (Retarder). Lengthens thickening time.
0.3% CFR (dispersant). Makes cement easier to mix.
Tail (Type H Cement): 0.25-0.40% Lignosulfonate (Retarder). Lengthens thickening time.
0.2-0.3% CFR (dispersant). This is to make the cement easier to mix.
60 % Calcuim Carbonate. Acid solubility.
0.4-0.6% Halad (fluid loss). Reduces amount of water lost to formation.
25) Proposed borehole conditioning procedures. <u>Surface</u> : Circulate hole clean (Approximately 30-45 minutes) rotating & reciprocating
one full joint until cuttings diminish at surface. When cuttings returning to surface diminish, continue to circulate an additional 5
minutes. To ensure that there is no fill, short trip two stands with no circulation. If there is fill, bring compressors back on
and circulate hole clean. A constant rate of higher than expected cuttings volume likely indicates washouts that will not clean up.
Intermediate: Circulate hole clean (Approximately 30-45 minutes) rotating & reciprocating one full joint until cuttings diminish at
surface. When cuttings returning to surface diminish, continue to circulate an additional 5 minutes. If foam drilling, to enhance
hole cleaning use a soap sweep or increase injection rate & foam concentration.
Production: Pump marker sweep with nut plug to determine actual hole washout. Calculate a gauge holes bottoms up volume.
Perform a cleanup cycle by pumping 3-5 bottoms up or until the shakers are clean. Check volume of cuttings coming across
the shakers every 15 minutes.

*Note: Attach additional sheets as needed.

Page 3 of 3

RECEIVED
Office of Oil and Gas

OCT 242013

WV Department of Environmental Protection

Well Schematic EQT Production

8,000' —


Elevation KB: 514385 (PNG129H12) Well Name Target Prospect Azimuth Wetzel West Virgina Vertical Section 4295 **—** 0' 0' -Hole Size 24" - 20" Conductor at 40' Bit Size 17.5" 500' -- 500' TOC @ Surface 731' Fresh Water Base 13 3/8", MC-50, 54.5# @ 831' ft MD 1,000' — 905' Base Red Rock Bit Size 12.375" **—** 1,000' **—** 1,500' 1,500' — **—** 2,000° 2.000' -2,179' Maxton 2,500' — ^{2,416'} Big Lime - 2.500 2,654' Weir 2.852' -Gantz 2,969 -Fifty foot 3,000' — 3,042' -Thirty foot **—** 3,000' 3,089' -Gordon 3,208' -Forth Sand 3,343' -Bayard 3,385' Int. csg pt TOC @ Surface 9 5/8", MC-50, 40# @ Bit Size 8.5" 3,500' — **—** 3,500' 3,760' -Warren 3,886' -Speechley 4,000' — **-** 4,000' **—** 4,500° 4,500' — 4,760' -Riley **—** 5,000' 5,000' — 5,371' -Benson 5.500' -- 5.500 5,739' -Alexander 6.000' — - 6,000 6.500' -**—** 6,500' KOP = 4,145' ft MD 7,000' — 7,051' -Middlesex **—** 7,000' 10 Deg DLS 7,091' -Genesee 7,173' -Geneseo 7,198' -Tully Land @ 8,588' ft MD 7,318' ft TVD 7,500' — 7,214' -Hamilton 7,297' -Marcellus 7,348' Onondaga **-** 7,500' 5 1/2", P-110, 20# 11,339' ft MD 7,318' ft TVD

— 8,000'

RECEIVED
Office of Oil and Gas

OCT 242013

WV Department of Environmental Protection



WW-9 (5/13)

P	age	of	
API No. 47	103	 02971	0
Operator's We	ell No.	514	385

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS

Fluids/Cuttings Disposal & Reclamation Plan

Operator Name	F	NG129	0	P Code	
Watershed (HUC10)Upper Run of South	Fork of Fishing Cree	ek Quadrar	ngle	Pine Grove
Elevation	1328.0	_ County	Wetzel	District	Grant
Do you anticipate u	sing more than 5,000	bbls of water to	complete the prop	osed well wo	rk? Yes <u>x</u> No
If so please	Yes: No: describe anticipated p etic liner be used in the	it waste:	No	X If so,	what ml.?60
Proposed ————————————————————————————————————	Reuse (a	cation nd Injection API Number sposal (Supp	tes: (UIC Permit Num ly form WW-9 for	disposal loca	tion)
	stem be used? Ye				om the drilling
If oil bas Additives to be used	nticipated for this well ed, what type? Synth d in drilling medium? sal method? Leave ir	etic, petroleum, e MILBAR, Viscosife Deflocculant, Lub	etc r, Alkalinity Control, Lime, Ch ricant, Detergent, Defoaming	nloride Salts,Rate Filtra , Walnut Shell, X-Cide	ation Control,
	oit and plan to solidify wha	1551 10			n/a
- Landfill o	r offsite name/permit n	umber?	Se	ee Attached Li	st
on August 1, 2005, by the provisions of the permit or regulation can lead to I certify under per application form and all the information, I believe	yped Name)	the West Virginia De olations of any term of sonally examined and nat, based on my inque, accurate, and com	partment of Environm or condition of the gen d am familiar with the uiry of those individua plete. I am aware tha	nental Protection. peral permit and/or information subn is immediately re t there are signifi	I understand that the or other applicable law nitted on this sponsible for obtaining
Subscribed and swo	orn before me this	da	y of <u>OCTの</u>	EK	, 20 <u>/ 3</u> Notary Public
My commission exp	ilres	6/27/	2018		

Notary Public, State Of West Virginia
NICHOLAS L. BUMGARDNER
Rt. 1 Box 4
Liberty, WV 25124
My Commission Expires June 27, 2018

Office of Oil and Gas

OCT 242013

, ,		Operator	's Well No.	514385
Proposed Revegetatio	n Treatment: Acres Disturb	ed no additional disturbance	Prevegetation pH _	6.4
Lime	3 Tons/acre	or to correct to pH	6.5	
Fertilize type		-		
Fertilizer Amo	ount1/3	lbs/acre (500 lbs minimum)		
Mulch	2	Tons/acre		
•		Seed Mixtures		
			Permanent	
• •	lbs/acre 40	Seed Type Orchard Grass	lbs/a 15	cre
Alsike Clover	5	Alsike Clover	5	
Annual Rye	15			
AMarka				
	cation,pit and proposed area	a for land application.		
Photocopied section of	f involved 7.5' topographic s	sheet.		
Plan Approved by:	1/			
•				
Fertilize type Fertilizer Amount 1/3 Ibs/acre (500 lbs minimum) Mulch 2 Tons/acre Seed Mixtures Temporary Seed Type KY-31 40 Orchard Grass Alsike Clover Annual Rye 15 Attach: Drawing(s) of road, location,pit and proposed area for land application. Photocopied section of involved 7.5' topographic sheet.				
Title: $Oilt + G$	es Inspector			
Field Deviewad0	, /	Voc. /) No	

RECEIVED

Office of OT and Gas

MGV 012013

EQT Production Water plan Offsite disposals for Marcellus wells

CWS TRUCKING INC.

P.O. Box 391 Williamstown, WV 26187 740-516-3586 Noble County/Noble Township Permit # 3390

LAD LIQUID ASSETS DISPOSAL INC.

226 Rankin Road Washington, PA 15301 724-350-2760 724-222-6080 724-229-7034 fax Ohio County/Wheeling Permit # USEPA WV 0014

TRI COUNTY WASTE WATER MANAGEMENT, INC.

1487 Toms Run Road Holbrook, PA 15341 724-627-7178 Plant 724-499-5647 Office Greene County/Waynesburg Permit # TC-1009

Waste Management - Meadowfill Landfill

Rt. 2, Box 68 Dawson Drive Bridgeport, WV 26330 304-326-6027 Permit #SWF-1032-98 Approval #100785WV

Waste Management - Northwestern Landfill

512 E. Dry Road Parkersburg, WV 26104 304-428-0602 Permit #SWF-1025 WV-0109400 Approval #100833WV

BROAD STREET ENERGY LLC

37 West Broad Street Suite 1100 Columbus, Ohio 43215 740-516-5381 Washington County/Belpre Twp. Permit # 8462

TRIAD ENERGY

P.O. Box 430 Reno, OH 45773 740-516-6021 Well 740-374-2940 Reno Office Jennifer Nobel County/Jackson Township Permit # 4037

KING EXCAVATING CO.

Advanced Waste Services 101 River Park Drive New Castle, Pa. 16101 Facility Permit# PAR000029132

RECEIVED
Office of Oil and Gas

OCT 242013

WV Department of Environmental Protection

west virginia department of environmental protection



Water Management Plan: Primary Water Sources



WMP-01591

API/ID Number:

047-103-02971

Operator:

EQT Production Company

514385

Important:

For each proposed primary water source (including source intakes for purchased water sources) identified in your water management plan, and summarized herein, DEP has made an evaluation concerning water availability over the specified date range. DEP's assessment is based on the following considerations:

- •Statistical analysis of historical USGS stream gauge data (transferred to un-gauged locations as necessary);
- •Identification of sensitive aquatic life (endangered species, mussels, etc.);
- Quantification of known existing demands on the water supply (Large Quantity Users);
- •Minimum flows required by the Army Corps of Engineers; and
- · Designated stream uses.

Based on these factors, DEP has provided, for each intake location (and origination point for purchased water), a reference gauge location and discharge flow reading which must be surpassed prior to withdrawals. Additionally, DEP has established a minimum passby flow at the withdrawal location which must also be surpassed prior to withdrawals. These thresholds are considered terms of the permit and are enforceable as such.

DEP is aware that some intake points will be used for mutiple wells and well sites. In these cases, the thresholds set by the Water Management Plan are to be interepreted as total withdrawal limits for each location over the specified date range regardless of how many wells are supported by that intake.

For all purchased water intakes, determinations of water availability are made at the original source intake location. It is the responsibility of the Oil and Gas Operator, not the seller, to cease withdrawal of water from the seller when flows are less than the minimum gauge reading at the stream gauge referenced by the Water Management Plan in order to protect stream uses.

Note that the determinations made herein are based on the best available data, but it is impossible to predict water availability in the future. While the DEP has carefully established these minimum withdrawal thresholds, it remains the operator's responsibility to protect aquatic life at all times. Approval to withdrawal is contingent upon permission from the land owner. It is the responsibility of the operator to secure and maintain permission prior to any withdrawals.

The operator is reminded that 24-48 hours prior to withdrawing (or purchasing) water, DEP must be notified by email at DEP.water.use@wv.gov.

APPROVED NOV 2 1 2013

Source Summary

WMP-01591

API Number:

047-103-02971

Operator:

EQT Production Company

514385

Stream/River

Ohio River at Hannibal, OH Source

Wetzel

Owner:

Richard Potts/Rich

Merryman

Start Date

End Date

Total Volume (gal)

Max. daily purchase (gal)

Intake Latitude: Intake Longitude:

11/1/2013

11/1/2014

4,700,000

39.655883

-80.86678

✓ Regulated Stream?

Ohio River Min. Flow

Ref. Gauge ID:

9999999

Ohio River Station: Willow Island Lock & Dam

Max. Pump rate (gpm):

1,500

Min. Gauge Reading (cfs):

6,468.00

Min. Passby (cfs)

DEP Comments:

Refer to the specified station on the National Weather Service's Ohio River forecast

website: http://www.erh.noaa.gov/ohrfc//flows.shtml

Source

S. Fork of Fishing Creek @ Hastings Truck Pad

Wetzel

Owner:

Dominion Transmission

Start Date

End Date

Total Volume (gal)

Max. daily purchase (gal)

39.553

Intake Latitude: Intake Longitude: -80.669

11/1/2013

11/1/2014

4,700,000

3114500

MIDDLE ISLAND CREEK AT LITTLE, WV

Max. Pump rate (gpm):

☐ Regulated Stream?

1,260

Min. Gauge Reading (cfs):

Ref. Gauge ID:

78.05

Min. Passby (cfs)

10.32

DEP Comments:

Source

S. Fork of Fishing Creek @ Jacksonburg Truck Pad

Wetzel

Owner:

Ronald Anderson

Start Date

End Date

Total Volume (gal)

Max. daily purchase (gal)

Intake Latitude: Intake Longitude: 39.52609

-80.6338

11/1/2013

11/1/2014

4,700,000

3114500

MIDDLE ISLAND CREEK AT LITTLE, WV

Max. Pump rate (gpm):

☐ Regulated Stream?

1,260

Min. Gauge Reading (cfs):

Ref. Gauge ID:

73.12

Min. Passby (cfs)

8.86

DEP Comments:

0	Source	N. Fork of Fishi	ng Creek @	Pine Grove Truck Pad	I	Wetzel	Owner: T	own of Pine Grove
	Start Date 11/1/2013	End Date 11/1/2014		Total Volume (gal) 4,700,000	Max. daily p	ourchase (gal)	Intake Latitude: 39.571562	Intake Longitude: -80.677848
	☐ Regulated	Stream?		Ref. Gauge II	D: 31145	00	MIDDLE ISLAND CREEK AT	LITTLE, WV
	Max. Pump r	rate (gpm):	2,520	Min. Gauge Read	ing (cfs):	85.35	Min. Passby (c	fs) 6.22
		DEP Commer	nts:					
0	Source	N. Fork of Fishi	ng Creek @	Edgell Property		Wetzel	Owner:	Cathy Edgell
	Start Date 11/1/2013	End Date 11/1/2014		Total Volume (gal) 4,700,000	Max. daily p	ourchase (gal)	Intake Latitude: 39.58191	Intake Longitude: -80.622839
	☐ Regulated	Stream?		Ref. Gauge II	D: 31145	00	MIDDLE ISLAND CREEK AT	LITTLE, WV
	Max. Pump	rate (gpm):	1,260	Min. Gauge Read	ing (cfs):	78.74	Min. Passby (c	fs) 5.76
		DEP Comme	nts:					
0	Source	N. Fork of Fish	ing Creek @	Lydick Property		Wetzel	Owner:	Les Lydick
	Start Date 11/1/2013	End Date 11/1/2014		Total Volume (gal) 4,700,000	Max. daily p	ourchase (gal)	Intake Latitude: 39.57795	Intake Longitude: -80.59221
	☐ Regulated	Stream?		Ref. Gauge II	D: 31145	00	MIDDLE ISLAND CREEK AT	LITTLE, WV
	Max. Pump ı	rate (gpm):	1,260	Min. Gauge Read	ing (cfs):	75.93	Min. Passby (c	fs) 3.28


DEP Comments:

Source	N. Fork of Fish	ing Creek @	BIG176 Pad		Wetzel	Owner:	John W. Kilcoyne
Start Date 11/1/2013			Total Volume (gal) 4,700,000	Max. daily p	ourchase (gal)	Intake Latitude: 39.560283	Intake Longitude: -80.560763
Regulated	Stream?		Ref. Gauge I	D: 311450	00	MIDDLE ISLAND CREEK AT	LITTLE, WV
Max. Pump	rate (gpm):	1,260	Min. Gauge Read	ling (cfs):	73.12	Min. Passby (c	fs) 2.19
	DEP Comme	nts:					
Source	N. Fork of Fish	ing Creek @	P Big 57 Pad		Wetzel	Owner:	EQT Corporation
Start Date 11/1/2013	End Date 11/1/2014		Total Volume (gal) 4,700,000	Max. daily p	ourchase (gal)	Intake Latitude: 39.55316	Intake Longitude: -80.53064
Regulated	I Stream?		Ref. Gauge I	D: 311450	00	MIDDLE ISLAND CREEK AT	LITTLE, WV
Max. Pump	rate (gpm):	1,260	Min. Gauge Read	ling (cfs):	70.31	Min. Passby (c	fs) 1.71
	DEP Comme	nts:					
			Source	e Summar	L		
	WMP-01591		API Number:	047-103-0	2971	Operator: EQT Produ	ction Company
		and trailing to the		514385			Α
Purchased	d Water					6.	
Source	HG Energy Wa	ter Supply \	Well		Wetzel	Owner:	HG Energy LLC
Start Date 11/1/2013	End Date 11/1/2014		Total Volume (gal) 4,700,000	Max. daily p	ourchase (gal) ,000	Intake Latitude: 39.61861	Intake Longitude: -80.87972
▼ Regulated	Stream? Oh	nio River Mi	n. Flow Ref. Gauge I	D: 999999	99 Oh	io River Station: Willow Isla	ind Lock & Dam
Max. Pump	rate (gpm):		Min. Gauge Read	ling (cfs):	6,468.00	Min. Passby (c	fs)
	DEP Commer	nts:					

			Source Detail		
	WMP-C	1591	API/ID Number: 047-10. 514385	3-02971 Operator: EQT Production	Company
ource ID): 30129 Sou	ırce Name HG Er	nergy Water Supply Well	Source Latitude: 39.618	61
		HG Er	nergy LLC	Source Longitude: -80.879	972
	HUC-8 Code:	5030201			/ . /
	Drainage Area	(sq. mi.): 2500	0 County: Wetzel		11/1/2013
□ Enc	dangered Species				11/1/2014
	ut Stream?	☐ Tier 3?	ream:	Total Volume from Source (gal):	4,700,000
	gulated Stream?	Ohio River N	/lin. Flow	Max. Pump rate (gpm):	
	ximate PSD?	0.110 1.1101 1.		Max. Simultaneous Tru	ucks:
	uged Stream?			Max. Truck pump rate (g	gpm)
Gue	abed Stream.				
	Reference Gaug	9999999	Ohio River Station: Willow Isla	nd Lock & Dam	
	Drainage Area (sc	ı. mi.) 25,00	00.00	Gauge Threshold (cfs):	6468
	Median	Threshold	<u>Estimated</u>		
<u>Ionth</u>	monthly flow (cfs)	(+ pump	Available water (cfs)		
1	45,700.00		water (cis)		
2	49,200.00				
3	65,700.00		-		
4	56,100.00		-		
5	38,700.00				
6	24,300.00 16,000.00		,		
7	13,400.00		n -		
9	12,800.00				
10	15,500.00				
11	26,300.00	-	-		
12	41,300.00	-			
	١٨	Jater Availa	bility Profile	Water Availability Assessmen	t of Locatio
		racer revails	iomey i rome	Base Threshold (cfs):	
80000) ———			Upstream Demand (cfs):	0.00
		^		Downstream Demand (cfs):	0.00
60000	Flow on th		gulated by the Army Corps	S OT	0.00
40000	Engineers	. Please adher	e to the stated thresholds	Pump rate (cfs):	
	maintain t	he minimum g	uaranteed flow requireme	Headwater Safety (cfs):	0.00
20000	,			Ungauged Stream Safety (cfs):	0.00
C) +	1 1 1			
	1 2	3 4 5	6 7 8 9 10 1	Min. Gauge Reading (cfs):	
	क्रमं स्थापना । । । । । । । । । । । । । । । । । । ।	March 86 M235.0	ese () 2560 PDA 20077 27	Passby at Location (cfs):	
		Madian Man	thly Flow _ Throshold	rassuy at Lucation (CIS):	

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

◆ Median Monthly Flow ■ Threshold



8

7

Median Monthly Flow — Threshold

9

10

11

12

20000

1

2

3

4

5

6

0.00

Ungauged Stream Safety (cfs):


Min. Gauge Reading (cfs):

Passby at Location (cfs):

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

WMP-01591	API/ID Number	: 047-103-02971	Operator: EQT Produc	tion Company
		514385		
ource ID: 30120 Source Name	S. Fork of Fishing Creek	@ Hastings Truck Pad	Source Latitude: 39.	.553
	Dominion Transmission		Source Longitude: -80	0.669
HUC-8 Code: 5030 Drainage Area (sq. mi.): ☐ Endangered Species? ✓ Mu	70.02 County:	Wetzel	Anticipated withdrawal start date: Anticipated withdrawal end date: Total Volume from Source (gal):	11/1/2013 11/1/2014 4,700,000
Regulated Stream?	r 3?		Max. Pump rate (gpm):	1,260
☐ Proximate PSD? ☐ Gauged Stream?		= = - 1	Max. Truck pump r	
Reference Gaug 31145	MIDDLE ISLAND	CREEK AT LITTLE, WV		
Drainage Area (sq. mi.)	458.00		Gauge Threshold (cfs):	45

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	75.09	20.87	54.35
2	94.45	20.87	73.72
3	105.69	20.87	84.95
4	78.48	20.87	57.75
5	41.40	20.87	20.66
6	14.46	20.87	-6.28
7	8.18	20.87	-12.56
8	6.74	20.87	-14.00
9	3.45	20.87	-17.29
10	4.33	20.87	-16.40
11	21.17	20.87	0.43
12	51.72	20.87	30.99




Water Availability Assessment of	f Location
Base Threshold (cfs):	6.88
Upstream Demand (cfs):	7.74
Downstream Demand (cfs):	0.00
Pump rate (cfs):	2.81
Headwater Safety (cfs):	1.72
Ungauged Stream Safety (cfs):	1.72
Min. Gauge Reading (cfs):	78.05
Passby at Location (cfs):	10.32

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

WMP-01591	API/ID Number: 047-103-	02971 Operator:	EQT Product	ion Company
	514385			
ource ID: 30121 Source Name S. Fork	of Fishing Creek @ Jacksonburg	Truck Pad Source	Latitude: 39.	52609
Ronald	Anderson	Source Lo	ongitude: -80.	.6338
HUC-8 Code: 5030201 Drainage Area (sq. mi.): 45.72	County: Wetzel	Anticipated withdrawal		11/1/2013
☐ Endangered Species? ✓ Mussel Stre	1000 (100 (100 (100 (100 (100 (100 (100	Anticipated withdrawa Total Volume from S		11/1/2014 4,700,000
☐ Trout Stream? ☐ Tier 3? ☐ Regulated Stream?		Max. Pump	rate (gpm):	1,260
Proximate PSD?			Max. Simultaneou	s Trucks: 0
Gauged Stream?		M	ax. Truck pump ra	te (gpm) 0
Reference Gaug 3114500	MIDDLE ISLAND CREEK AT LITTL	E, WV		
Drainage Area (sq. mi.) 458.0	0	Gauge Thr	eshold (cfs):	45

<u>Month</u>	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	49.03	12.36	37.12
2	61.67	12.36	49.76
3	69.01	12.36	57.10
4	51.25	12.36	39.33
5	27.03	12.36	15.12
6	9.44	12.36	-2.47
7	5.34	12.36	-6.57
8	4.40	12.36	-7.51
9	2.25	12.36	-9.66
10	2.83	12.36	-9.08
11	13.82	12.36	1.91
12	33.77	12.36	21.86



Passby at Location (cfs):	8.86
Min. Gauge Reading (cfs):	73.12
Ungauged Stream Safety (cfs):	1.12
Headwater Safety (cfs):	1.12
Pump rate (cfs):	2.81
Downstream Demand (cfs):	2.12
Upstream Demand (cfs):	2.81
Base Threshold (cfs):	4.49

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

API/ID Number: 047-103-02971 Operator: **EQT Production Company** WMP-01591 514385 Source Name N. Fork of Fishing Creek @ Pine Grove Truck Pad Source ID: 30122 Source Latitude: 39.571562 Source Longitude: -80.677848 Town of Pine Grove HUC-8 Code: 5030201 11/1/2013 Anticipated withdrawal start date: Drainage Area (sq. mi.): 42.17 County: Wetzel 11/1/2014 Anticipated withdrawal end date: **Endangered Species?** ✓ Mussel Stream? 4,700,000 Total Volume from Source (gal): Trout Stream? ☐ Tier 3? 2,520 Max. Pump rate (gpm): Regulated Stream? Max. Simultaneous Trucks: Proximate PSD? Pine Grove Max. Truck pump rate (gpm) Gauged Stream? MIDDLE ISLAND CREEK AT LITTLE, WV Reference Gaug 3114500 458.00 45 Drainage Area (sq. mi.) Gauge Threshold (cfs):

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	45.22	24.07	21.25
2	56.89	24.07	32.91
3	63.65	24.07	39.68
4	47.27	24.07	23.29
5	24.93	24.07	0.96
6	8.71	24.07	-15.27
7	4.93	24.07	-19.05
8	4.06	24.07	-19.92
9	2.08	24.07	-21.90
10	2.61	24.07	-21.37
11	12.75	24.07	-11.23
12	31.15	24.07	7.17

Water Availability Profile 80 60 40 20 0 1 2 3 4 5 7 8 9 10 11 12 6 Median Monthly Flow — Threshold

	4.4.4
Base Threshold (cfs):	4.14
Upstream Demand (cfs):	12.24
Downstream Demand (cfs):	0.00
Pump rate (cfs):	5.61
Headwater Safety (cfs):	1.04
Ungauged Stream Safety (cfs):	1.04
Min. Gauge Reading (cfs):	85.35

Passby at Location (cfs):


Water Availability Assessment of Location

6.22

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

WMP-01591	API/ID Number: 047-103-029	Operator: EQT Product	tion Company
	514385		
	k of Fishing Creek @ Edgell Property Edgell		58191 .622839
HUC-8 Code: 5030201 Drainage Area (sq. mi.): 32.23 □ Endangered Species?		Anticipated withdrawal start date: Anticipated withdrawal end date: Total Volume from Source (gal): Max. Pump rate (gpm): Max. Simultaneou Max. Truck pump rate	
Reference Gaug 3114500 Drainage Area (sq. mi.) 458	MIDDLE ISLAND CREEK AT LITTLE, \	NV Gauge Threshold (cfs):	45

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	34.56	15.99	18.59
2	43.48	15.99	27.51
3	48.65	15.99	32.68
4	36.13	15.99	20.16
5	19.06	15.99	3.09
6	6.65	15.99	-9.32
7	3.77	15.99	-12.20
8	3.10	15.99	-12.87
9	1.59	15.99	-14.38
10	2.00	15.99	-13.98
11	9.74	15.99	-6.23
12	23.81	15.99	7.84




Water Availability Assessment of	f Location
Base Threshold (cfs):	3.17
Upstream Demand (cfs):	8.43
Downstream Demand (cfs):	1.00
Pump rate (cfs):	2.81
Headwater Safety (cfs):	0.79
Ungauged Stream Safety (cfs):	0.79
Min. Gauge Reading (cfs):	78.74
Passby at Location (cfs):	5.75

"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

WMP-01591 API/ID Number: 047-103-02971 Operator: **EQT Production Company** 514385 Source ID: 30124 N. Fork of Fishing Creek @ Lydick Property Source Latitude: 39.57795 Source Name Les Lydick Source Longitude: -80.59221 5030201 HUC-8 Code: Anticipated withdrawal start date: 11/1/2013 15.46 Wetzel Drainage Area (sq. mi.): County: Anticipated withdrawal end date: 11/1/2014 **Endangered Species?** ✓ Mussel Stream? Total Volume from Source (gal): 4,700,000 Trout Stream? ☐ Tier 3? 1,260 Max. Pump rate (gpm): Regulated Stream? Max. Simultaneous Trucks: Proximate PSD? 0 Max. Truck pump rate (gpm) Gauged Stream? Reference Gaug 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV 458.00 45 Drainage Area (sq. mi.) Gauge Threshold (cfs):

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	16.58	10.71	6.04
2	20.86	10.71	10.32
3	23.34	10.71	12.80
4	17.33	10.71	6.79
5	9.14	10.71	-1.40
6	3.19	10.71	-7.34
7	1.81	10.71	-8.73
8	1.49	10.71	-9.05
9	0.76	10.71	-9.78
10	0.96	10.71	-9.58
11	4.67	10.71	-5.86
12	11.42	10.71	0.88





Water Availability Assessment of Location


Min. Gauge Reading (cfs): Passby at Location (cfs):	75.93 3.28
Ungauged Stream Safety (cfs):	0.38
Headwater Safety (cfs):	0.38
Pump rate (cfs):	2.81
Downstream Demand (cfs):	1.00
Upstream Demand (cfs):	5.62
Base Threshold (cfs):	1.52

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

API/ID Number: 047-103-02971 **EQT Production Company** WMP-01591 Operator: 514385 30125 N. Fork of Fishing Creek @ BIG176 Pad Source Latitude: 39.560283 Source ID: Source Name Source Longitude: -80.560763 John W. Kilcoyne 5030201 HUC-8 Code: 11/1/2013 Anticipated withdrawal start date: 8.09 Wetzel Drainage Area (sq. mi.): County: 11/1/2014 Anticipated withdrawal end date: **Endangered Species?** ✓ Mussel Stream? Total Volume from Source (gal): 4,700,000 Trout Stream? ☐ Tier 3? 1,260 Max. Pump rate (gpm): Regulated Stream? Max. Simultaneous Trucks: 0 Proximate PSD? Max. Truck pump rate (gpm) Gauged Stream? Reference Gaug 3114500 MIDDLE ISLAND CREEK AT LITTLE, WV 458.00 45 Drainage Area (sq. mi.) Gauge Threshold (cfs):

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	8.68	6.81	2.21
2	10.91	6.81	4.45
3	12.21	6.81	5.75
4	9.07	6.81	2.60
- 5	4.78	6.81	-1.68
6	1.67	6.81	-4.79
7	0.95	6.81	-5.52
8	0.78	6.81	-5.69
9	0.40	6.81	-6.07
10	0.50	6.81	-5.96
11	2.45	6.81	-4.02
12	5.98	6.81	-0.49





Water Availability Assessment of Location


Passby at Location (cfs):	2.19
Min. Gauge Reading (cfs):	73.12
Ungauged Stream Safety (cfs):	0.20
Headwater Safety (cfs):	0.20
Pump rate (cfs):	2.81
Downstream Demand (cfs):	1.00
Upstream Demand (cfs):	2.81
Base Threshold (cfs):	0.79

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

WMP-01591	API/ID Number:	047-103-02971	Operator:	EQT Product	ion Company
	51	4385			
Source ID: 30126 Source Name N. For	rk of Fishing Creek @ B	lig 57 Pad	Source	ce Latitude: 39.	55316
EQT C	T Corporation		Source Longitude: -80.53064		
HUC-8 Code: 5030201 Drainage Area (sq. mi.): 4.77 □ Endangered Species? ✓ Mussel St □ Trout Stream? □ Tier 3? □ Regulated Stream?	county.	Netzel	anticipated withdraw Anticipated withdraw Total Volume from Max. Pum	wal end date: Source (gal): p rate (gpm):	11/1/2013 11/1/2014 4,700,000 1,260
Proximate PSD? Gauged Stream?			Max. Simultaneous Trucks: 0 Max. Truck pump rate (gpm) 0		
Reference Gaug 3114500	MIDDLE ISLAND CRE	EK AT LITTLE, WV			
Drainage Area (sq. mi.) 458	3.00		Gauge T	hreshold (cfs):	45

Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	5.12	3.51	1.62
2	6.43	3.51	2.94
3	7.20	3.51	3.71
4	5.35	3.51	1.85
5	2.82	3.51	-0.67
6	0.98	3.51	-2.51
7	0.56	3.51	-2.93
8	0.46	3.51	-3.03
9	0.24	3.51	-3.26
10	0.30	3.51	-3.20
11	1.44	3.51	-2.05
12	3.52	3.51	0.03

Water Availability Profile



Min. Gauge Reading (cfs): Passby at Location (cfs):	70.31 1.70				
Ungauged Stream Safety (cfs):	0.12				
Headwater Safety (cfs):	0.12				
Pump rate (cfs):	2.81				
Downstream Demand (cfs):	1.00				
Upstream Demand (cfs):	0.00				
Base Threshold (cfs):	0.47				
Water Availability Assessment of Location					

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

west virginia department of environmental protection



Water Management Plan: **Secondary Water Sources**



WMP-01591

API/ID Number

047-103-02971

Operator:

EQT Production Company

514385

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Ground Water

Source ID: 30127 Source Name

Groundwater Well TW#1

Source start date:

11/1/2013

Source end date:

11/1/2014

Source Lat:

39.56059

Source Long:

-80.56027

County

Wetzel

Max. Daily Purchase (gal)

Total Volume from Source (gal):

4,700,000

DEP Comments:

WMP-01591 API/ID Number 047-103-02971 Operator: EQT Production Company

514385

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Groundwater Well TW#5 Source ID: 30128 Source Name 11/1/2013 Source start date: 11/1/2014 Source end date: 39.553434 -80.528871 Wetzel Source Lat: Source Long: County 4,700,000 Max. Daily Purchase (gal) Total Volume from Source (gal): **DEP Comments:**

514385

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Multi-site impoundment

YOHO Centralized Freshwater Impoundment Source ID: 30130 Source Name

11/1/2013 Source start date:

Source end date:

11/1/2014

Source Lat:

39.56092

Source Long:

-80.61432

County

Wetzel

Max. Daily Purchase (gal)

Total Volume from Source (gal):

4,700,000

DEP Comments:

103-FWC-00001

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-1068

Source ID: 30131 Source Name

Carlin Centralized Freshwater Impoundment

Source start date:

11/1/2013

Source end date:

11/1/2014

Source Lat:

39.51168

Source Long:

-80.598605

County

Wetzel

Max. Daily Purchase (gal)

Total Volume from Source (gal):

4,700,000

DEP Comments:

103-FWC-00002

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-1321

WMP- 01591	API/ID Number	047-103-02971	Operator:	EQT Production Company
-------------------	---------------	---------------	-----------	-------------------------------

514385

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable). DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

BIG176 Centralized Freshwater Impoundment Source ID: 30132 Source Name 11/1/2013 Source start date:

11/1/2014 Source end date:

Wetzel 39.561403 -80.561554 Source Long: County Source Lat:

Total Volume from Source (gal): 4,700,000 Max. Daily Purchase (gal)

DEP Comments: 103-FWC-00003

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Sycoc Centralized Freshwater Impoundment Source ID: 30133 Source Name Source start date:

11/1/2013 11/1/2014 Source end date:

39.56436 -80.625644 County Wetzel Source Lat: Source Long:

4,700,000 Total Volume from Source (gal): Max. Daily Purchase (gal)

DEP Comments: 103-FWC-00004

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-1222

Reference: WMP-1322

WMP-01591 API/ID Number 047-103-02971 Operator: EQT Production Company

514385

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Source ID: 30134 Source Name Mobiley Centralized Freshwater Impoundment Source start date: 11/1/2013

Source end date: 11/1/2014

Source Lat: 39.553653 Source Long: -80.52971 County Wetzel

Max. Daily Purchase (gal)

Total Volume from Source (gal): 4,700,000

DEP Comments: 103-FWC-00006

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

agement plan. The Reference: WMP-1534

Source ID: 30135 Source Name Richwood Centralized Freshwater Impoundment Source start date: 11/1/2013

Source end date: 11/1/2014

Source Lat: 39.551137 Source Long: -80.605342 County Wetzel

Max. Daily Purchase (gal)

Total Volume from Source (gal): 4,700,000

DEP Comments: 103-FWC-00007

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-1535

WMP-01591 API/ID Number 047-103-02971 Operator: EQT Production Company

514385

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Recycled Frac Water

Source ID: 30136 Source Name Various Source start date: 11/1/2013

Source end date: 11/1/2014

Source Lat: Source Long: County

Max. Daily Purchase (gal) Total Volume from Source (gal): 4,700,000

DEP Comments:

